


## 150T Fixed Displacement Vane Pumps

### Specification



Symbol



| Model    | Displacement<br>(L/min) |       |       |       | Allowable speed<br>(r.p.m) |      | Max.<br>pressure<br>(kgf/cm <sup>2</sup> ) | Weight<br>(kg) |             |
|----------|-------------------------|-------|-------|-------|----------------------------|------|--------------------------------------------|----------------|-------------|
|          | Speed (rpm)             |       |       |       | Max.                       | Min. |                                            | Foot type      | Flange type |
|          | 1000                    | 1200  | 1500  | 1800  |                            |      |                                            |                |             |
| 150T-48  | 48.2                    | 57.9  | 72.4  | 86.9  | 1500                       | 600  | 70                                         | 26             | 25          |
| 150T-61  | 61.4                    | 73.8  | 92.2  | 110.7 | 1500                       | 600  | 70                                         | 26             | 25          |
| 150T-75  | 75                      | 90.6  | 113.2 | 135.9 | 1500                       | 600  | 70                                         | 26             | 25          |
| 150T-94  | 94                      | 113.0 | 141.3 | 169.5 | 1200                       | 600  | 70                                         | 26             | 25          |
| 150T-116 | 116.2                   | 139.6 | 174.0 | —     | 1200                       | 600  | 70                                         | 26             | 25          |