

DSHG Electric Controlled Hydraulic Operated Directional Control Valves



Symbol



How to order

DSHG	-06	-3C4	-A2	5	-P	D	-
Series	Specifica- tion	Spool type as page	Coil type A1: AC110V A2: AC220V A3: AC380V D1: DC12V D2: DC24V R1: RF110V R2: RF220V -: Omit -: Valve body only	Fre- quency 5: 50Hz 6: 60Hz DC Omit	Control type Omit Inner control (Standard) P: Outer control	Drain type Omit Inner drain (Standard) D: Outer drain	Prefix Omit (general) S: with stroke adjuster N: New type
DSHG:	04: NG16 (1/2")	25-26					
Terminal box							
DSHG-N: (DIN)	06: NG25 (3/4") 10: NG32 (1 1/4")						

Specification

Model	Rated flow (L/min)	Max. flow (L/min)	Max.operated pressure (kgf/cm ²)	Allowed back pressure (kgf/cm ²)	Max.operated frequencies (times/min)	Weight (kg)
DSHG-04	200	300	350	140	120	8.8
DSHG-06	300	500	350	140	120	13.7
DSHG-10	500	1100	350	140	120	45.3

Remark: max. flow differs with different spool types 3C5, 3C6 type's flow will be less.