


DMT、DMG、HV Hand Operated Directional Control Valves



符号
Symbol



How to order

DMG	02	3C2	W
Series number	Valve size	Spool type(as page 25-26)	Centered locking
HV	02	as 2B2 3C2 3C4 3C3 3C6	W: spring locking
DMT	03	But HV-03 series only 3C2	O: ball locking
DMG	04		
	06		
	10		

Specification

Model					Max. flow (L/min)			Max. operated pressure (kgf/cm ²)	Allowed back pressure (kgf/cm ²)	Weight (kg)		
DMT-W	DMT-O	DMG-W	DMG-O	Rotary	T	G	R			T	G	R
-	-	-	-	HV-03-3C2	-	-	30	70	20	-	-	3.0
-	-	DMG-02- ㊦㊦㊦	DMG-02- ㊦㊦㊦	-	-	30	-	250	100	-	1.5	-
DMT-03- ㊦㊦㊦	DMT-03- ㊦㊦㊦	DMG-03- ㊦㊦㊦	DMG-03- ㊦㊦㊦	-	50	50	-	250	100	4.5	3.7	-
DMT-04- ㊦㊦㊦	DMT-04- ㊦㊦㊦	-	-	-	100	-	-	250	140	7.6	-	-
DMT-06- ㊦㊦㊦	DMT-06- ㊦㊦㊦	-	-	-	180	-	-	250	140	13.0	-	-
DMT-10- ㊦㊦㊦	DMT-10- ㊦㊦㊦	-	-	-	300	-	-	250	140	22.0	-	-

Remark: max. flow differs with different spool types 3C3, 3C6 type's flow will be less.