

Hand Operated Directional Control Valves (Yuken Type)



How to order

F	DM	T	03	2
Special seals F: Phosphate ester	Series number DM:	Type of connection	Valve size	Number of valve position
		T: Thread	03 (RC3/8: PT 3/8) 06 (RC3/4: PT 3/4) 06X (RC1: PT 1) 10 (RC1 1/4: PT1 1/4) 10X (RC1 1/2: PT1 1/2)	
		G: Sub-plate	01 03	2

B	2	T	10
Spool-spring arrangement C: Spring center D: No spring location B: Spring bias	Spool type 2. 3. 4. 40. 5. 6. 60. 7. 8. 9. 10. 11. 12	Special two position valve T: Sub-plate	Design number 10

Specification

Model	Max. flow (L/min)				Max. operated pres. MPa	Max. T-line back pres. Mpa	Weight (kg)	
	7MPa	14MPa	21MPa	31.5MPa				
Sub-plate	DMG-01-3C ※ -10	35	35	35	-	25	14	1.8
	DMG-01-3D ※ -10	35	35	35	-	25	14	1.8
	DMG-01-2D ※ -10	35	35	35	-	25	14	1.8
	DMG-01-2B ※ -10	35	35	35	-	25	14	1.8
	DMG-03-3C ※ -50	100	100	100	-	25	16	4.0
	DMG-03-3D ※ -50	100	100	100	-	25	16	4.0
	DMG-03-2D ※ -50	100	100	100	-	25	16	4.0
	DMG-03-2B ※ -50	100	100	100	-	25	16	4.0