

KHB3K BK3 2-3 Screw-Type Ball Valves

How to order



| KHB3K(BK3) | G1/2 | 1 |
|--|---|---------------|
| code: KHB3K Boxshaped valve body DN04-25 | <p>Screw specification or tube bore as:</p> <p>a. FEMALE G1/2, none-threaded seal cylindrical pipe screw GB/T7037-1987 or ISO228.</p> <p>b. MALE M30x1.5, meet the standard of JB984-77 pipe joints(seal welded).</p> <p>c. 18LR pipe diameter is 18, FEMALE, meet standard of DIN2353, light type (sleeve type).</p> <p>d. 20SR pipe diameter is 20, FEMALE, meet standard of DIN2353, heavy type (sleeve type).</p> | <p>Symbol</p> |

| 1 | 1 | 1 | 2 | 01 | * |
|--|---|-----------------------------------|---|--|--|
| <p>Body, joint material</p> <p>1. Carbon</p> <p>4. Stainless steel</p> | <p>Sphare & controlled axle core material</p> <p>1. Alloy steel</p> <p>4. Stainless steel</p> | <p>Seal material</p> <p>1-POM</p> | <p>Joint & controlled axle core material</p> <p>2. NBR</p> <p>4. FPM</p> <p>Note: material 1112 is common compose, can be omitted</p> | <p>Handle type</p> <p>01 Cast Zinc with mounting bolt handle, crank</p> <p>02 Steal with mounting bolt handle, crank</p> | <p>Surface protection</p> <p>None: phosphating</p> <p>G: Cast Zinc</p> |